

# Safety Data Sheet

**Revision Number: 001.1** Issue date: 10/20/2022

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: KW-B

WAR

Product type:

Catalyst Longneck Bottle IDH number:

234796 Cyanoacrylate Item number: 30382 None identified **United States** Region:

Restriction of Use: Company address: Contact information: Mark V Lab Telephone: 860-653-7201

18 Kripes Rd. East Granby, CT 06026

Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

## 2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW	
RNING:	COMBUSTIBLE LIQUID.	
	CAUSES SKIN IRRITATION.	
	MAY CAUSE AN ALLERGIC SKIN REACTION.	
	CAUSES SERIOUS EYE IRRITATION	

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

MAY CAUSE RESPIRATORY IRRITATION.

#### PICTOGRAM(S)



#### **Precautionary Statements**

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors,

mist, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective

gloves, eye protection, and face protection.

IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and Response:

keep comfortable for breathing.

 $\overline{\text{IF IN}}$  EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or

carbon dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Ethyl 2-cyanoacrylate	7085-85-0	60 - 100
Methyl methacrylate polymer	9011-14-7	5 - 10

<sup>\*</sup> Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.
Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart
using a blunt instrument. If skin is burned due to the rapid generation of heat
by a large drop, seek medical attention. If lips are bonded, apply warm water
to the lips and encourage wetting and pressure from saliva in mouth. Peel or
roll lips apart. Do not pull lips apart with direct opposing force.

Eye contact:

Immediately flush with plenty of water for at least 15 minutes. Get medical

attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.

Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from

swallowing any separated mass.

Symptoms:

Ingestion:

See Section 11.

Notes to physician:

Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal bums they should be treated

symptomatically after adhesive is removed.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Dry powder. foam Carbon dioxide.

Special firefighting procedures: Fire fighters should wear positive pressure self-contained breathing apparatus

(SCBA).

Unusual fire or explosion hazards: Not available.

Hazardous combustion products: Trace amounts of toxic and/or irritating fumes may be released and the use of

breathing apparatus is recommended.

IDH number: 234796 Product name: Loctite® Super Glue Longneck Bottle

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Do not use cloths for mopping up. Flood with water to complete

polymerization and scrape off the floor. Cured material can be disposed of as

non-hazardous waste.

### 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of

this product. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal

burns.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethyl 2-cyanoacrylate	0.2 ppm TWA	None	None	None
Methyl methacrylate polymer	None	None	None	None

Engineering controls: Use positive down-draft exhaust ventilation if general ventilation is insufficient

to maintain vapor concentration below established exposure limits.

Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Safety goggles or safety glasses with side shields.

Eye/face protection:

Skin protection:

Respiratory protection:

Use nitrile gloves and aprons as necessary to prevent contact. Do not use

PVC, nylon or cotton.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:liquidColor:colourlessOdor:irritating

 Odor threshold:
 1 - 2 ppm

 pH:
 Not available.

 Vapor pressure:
 < 0.2 mm hg</td>

Boiling point/range: > 149 °C (> 300.2 °F)

Melting point/ range: Not available.

Vapor density: Approximate 3

Flash point: 80.0 - 93 °C (176°F - 199.4 °F) Tagliabue closed cup

Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available.

IDH number: 234796 Product name: Loctite® Super Glue Longneck Bottle

Autoignition temperature: 485 °C (905°F) Evaporation rate: Not available. **Solubility in water:** Polymerises in presence of water.

Partition coefficient (n-octanol/water): Not available.

VOC content: < 2 %; < 20 g/l (California SCAQMD Method 316B)

(Estimated)

Viscosity: Not available.

Decomposition temperature: Not available.

# 10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and

alcohols.

Hazardous decomposition

Hazardous reactions:

products:

None

Water, Amines, Alkalis, Alcohols.

Incompatible materials:

Not available.

Reactivity:

Spontaneous polymerization.

Conditions to avoid:

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### **Potential Health Effects/Symptoms**

Inhalation: Exposure to vapors above the established exposure limit results in respiratory irritation, which

may lead to difficulty in breathing and tightness in the chest.

**Skin contact:** Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause

allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the

skin. Cured adhesive does not present a health hazard even if bonded to the skin.

**Eye contact:** Irritating to eyes. Causes excessive tearing. Eyelids may bond.

Ingestion: Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It

is almost impossible to swallow.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Ethyl 2-cyanoacrylate	None	Irritant, Allergen, Respiratory
Methyl methacrylate polymer	None	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ethyl 2-cyanoacrylate	No	No	No
Methyl methacrylate polymer	No	No	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

IDH number: 234796 Product name: Loctite® Super Glue Longneck Bottle



Dispose of according to Federal, State and local governmental regulations. Recommended method of disposal:

Hazardous waste number: Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Combustible liquid, n.o.s. (Ethyl cyanoacrylate)

Hazard class or division: Combustible Liquid

Identification number: NA 1993 Packing group: Ш

International Air Transportation (ICAO/IATA)

Proper shipping name: Aviation regulated liquid, n.o.s. (Ethyl cyanoacrylate)

Hazard class or division:

Identification number: UN 3334

Packing group: Ш

Exceptions: Primary packs containing less than 500ml are unregulated by this mode of

transport and may be shipped unrestricted.

Exceptions: (Not more than 500ml) Unrestricted

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

# 15. REGULATORY INFORMATION

**United States Regulatory Information** 

All components are listed or are exempt from listing on the Toxic Substances Control Act TSCA 8 (b) Inventory Status:

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis **CERCLA/SARA Section 302 EHS:** None above reporting de minimis

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire, Reactive

**CERCLA/SARA Section 313:** None above reporting de minimis

No California Proposition 65 listed chemicals are known to be present.

California Proposition 65:

**Canada Regulatory Information** 

**CEPA DSL/NDSL Status:** 

Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Donna Houston, Regulatory Affairs Specialist

Issue date: 1/4/2016

IDH number: 234796 Product name: Loctite® Super Glue Longneck Bottle **DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.